

PHILIPS

RESPIRONICS



Especificaciones

Sistema General

Tasa de flujo	Hasta 10 LPM en incrementos de 1 litro l/min	Almacenamiento/Temperatura de transporte	-34 a 71 °C
Requisitos eléctricos	120V/60Hz (+/- 10%)	Temperatura de funcionamiento	13 a 32 °C
Garantía	Compresor estándar de un año/opcional de dos años (excluye compresor)/compresor opcional de dos años	Almacenamiento/Humedad de transporte	Hasta 95%, no condensante %
Indicador del porcentaje de oxígeno	Luz verde mayor que 82%/Luz amarilla entre 70-82%/Luz roja menor que 70%	Presión de operación	10 a 30 PSIG
Dimensiones	68.5x 48 x 33 cm	Indicadores de alarma	Alta presión del sistema/Baja presión del sistema/Falla de energía/Bajo nivel de oxígeno (modelo OPI disponible solo en el modelo M10605)/Sin flujo de oxígeno
Peso	92 +/- 4% @ 8-10 LPM; 94 +/- 2% @ 3-7 LPM; 92 +/- 4% @ 1-2 LPM		



Not all products are available in all the countries.
Please check with your local Philips Respironics representative for availability.

© 2016 Koninklijke Philips N.V. All rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

Broudy JS 3/16/16 MCI 4107399 PN 1127953
Customer Service 1300 766 488
www.philips.com.au